FACT SHEET

as required by LAC 33:IX.3109 for major LPDES facilities. for draft Louisiana Pollutant Discharge Elimination System Permit No. <u>LA0038709</u>; AI <u>19807</u>; <u>PER20070002</u> to discharge to waters of the State of Louisiana as per LAC 33:IX.2311.

The permitting authority for the Louisiana Pollutant Discharge Elimination System (LPDES) is:

Louisiana Department of Environmental Quality

Office of Environmental Services

P. O. Box 4313

Baton Rouge, Louisiana 70821-4313

I. THE APPLICANT IS:

City of DeQuincy

DeQuincy Wastewater Treatment Facility

P.O. Box 968

DeQuincy, LA 70663

II. PREPARED BY:

Eura DeHart

DATE PREPARED:

May 30, 2008

III. PERMIT ACTION:

reissue LPDES permit LA0038709, Al19807

LPDES application received: June 14, 2007

EPA has not retained enforcement authority.

LPDES permit issued: February 1, 2001 LPDES permit effective: March 1, 2001 LPDES permit expired: February 28, 2006

IV. <u>FACILITY INFORMATION:</u>

- A. The application is for the discharge of treated sanitary wastewater from an existing publicly owned treatment works serving the City of DeQuincy.
- B. The permit application does not indicate the receipt of industrial wastewater.
- C. The facility is located at the end of William Still Road in DeQuincy, Calcasieu Parish.
- D. The treatment facility consists of an extended aeration basin, two secondary clarifiers, and a tertiary filter. Disinfection is by ultraviolet light.
- E. Outfall 001

Discharge Location:

Latitude 30°26'15" North

Longitude 93°25'26" West

Description:

treated sanitary wastewater

LA0038709; AI19807; PER20070002

Page 2

Design Capacity:

1.1 MGD

Type of Flow Measurement which the facility is currently using:

Parshall Flume with Continuous Recorder

V. RECEIVING WATERS:

The discharge is into Buxton Creek, thence into the Houston River in segment 030806 of the Calcasieu River Basin.

Subsegment 030806 is listed on LDEQ's Final 2006 303(d) list as impaired for mercury for which the below TMDL has been developed. Subsegment 030806 was previously listed on LDEQ's Final 2006 303(d) list as impaired for organic enrichment/low DO for which the below TMDL has been developed. The Department of Environmental Quality reserves the right to impose more stringent discharge limitations and/or additional restrictions in the future to maintain the water quality integrity and the designated uses of the receiving waterbodies based on additional TMDL's and/or water quality studies. The DEQ also reserves the right to modify or revoke and reissue this permit based upon any changes to established TMDL's for this discharge, or to accommodate for pollutant trading provisions in approved TMDL watersheds as necessary to achieve compliance with water quality standards.

The following TMDL's have been established for Subsegment 030806:

<u>Houston River Watershed TMDL for Biochemical Oxygen-Demanding Substances (Subsegment</u> 030806) December 5, 2001

Per the TMDL, Buxton Creek and the City of DeQuincy were included in the model. "The DO criteria in the Houston River were met with the City of DeQuincy discharging at its current permit limits of 10/2 (CBOD₅/NH3-N). Therefore, its current permit limits will remain the same except for the addition of a 5.0 mg/L DO permit limit for its effluent."

Coastal Mercury TMDL

The City of Dequincy was identified in Appendix C of the TMDL as a point source discharge included in the TMDL. The City of Dequincy does not have a mercury limit in the current permit. However, the Coastal Mercury TMDL gives this facility a wasteload allocation for mercury.

It is the position of this Department that development and implementation of a Mercury Minimization Plan (MMP) will result in the most efficient reduction of mercury discharges to surface waters of Louisiana from domestic wastewater treatment facilities. Pollution prevention and waste minimization are more reasonably accomplished and cost productive than the implementation of controls and technologies to meet such stringent end-of-pipe mercury limitations as imposed by this TMDL. The MMP employs EPA approved analytical methods (EPA Methods 1631, 245.7) through effluent sampling and system wide monitoring programs to locate and identify potential sources of mercury in the treatment system. Once identified the MMP integrates cost-effective reduction controls, either treatment or prevention based, to reduce or eliminate mercury from the source.

Effluent monitoring data utilizing the more sensitive EPA approved test methods will be submitted as part of the MMP. Upon review of the MMP and subsequent annual reports, LDEQ reserves

LA0038709; A119807; PER20070002

Page 3

requirements in order to address mercury concerns.

The permittee shall develop and implement a Mercury Minimization Program Plan within one year of the effective date of the permit. Yearly thereafter, the permittee shall submit an annual report. See attached Mercury Minimization Guidance Document for additional information.

The critical low flow (7Q10) of the Buxton Creek is 0.20 cfs.

The hardness value is 119.0 mg/l and the fifteenth percentile value for TSS is 4.0 mg/l. (Memo dated May 21, 1999 from Mr. Max J. Forbes, Jr., Louisiana Department of Environmental Quality.)

The designated uses and degree of support for Segment 030806 of the Calcasieu River Basin are as indicated in the table below.¹

Overall Degree of Support for Segment 030806	Degree of Su	Degree of Support of Each Use									
Partial	Primary Contact Recreation	Secondary Contact Recreation	Propagation of Fish & Wildlife	Outstanding Natural Resource Water	Drinking Water Supply	Shell fish Propagation	Agriculture				
	Full	Full	Not Supported	N/A	N/A	N/A	Full				

^{1/} The designated uses and degree of support for Segment 030806 of the Calcasieu River Basin are as indicated in LAC 33:IX.1123.C.3, Table (3) and the 2004 Water Quality Management Plan, Water Quality Inventory Integrated Report, Appendix A, respectively.

VI. ENDANGERED SPECIES:

The receiving waterbody, Subsegment 030806 of the Calcasieu River Basin, is not listed in Section II.2 of the Implementation Strategy as requiring consultation with the U.S. Fish & Wildlife Service (FWS). This strategy was submitted with a letter dated October 24, 2007 from Boggs (FWS) to Brown (LDEQ). Therefore, in accordance with the Memorandum of Understanding between the LDEQ and FWS, no further informal (Section 7, Endangered Species Act) consultation is required. It was determined that the issuance of the LPDES permit is not likely to have an adverse effect on any endangered species or candidate species or the critical habitat. The effluent limitations established in the permit ensure protection of aquatic life and maintenance of the receiving water as aquatic habitat.

VII. HISTORIC SITES:

The discharge is from an existing facility location, which does not include an expansion beyond the existing perimeter. Therefore, there should be no potential effect to sites or properties on or eligible to for listing on the National Register of Historic Places, and in accordance with the

Fact Sheet <u>LA0038709</u>: Al<u>19807</u>; <u>PER20070002</u> Page 4

'Memorandum of Understanding for the Protection of Historic Properties in Louisiana Regarding LPDES Permits' no consultation with the Louisiana State Historic Preservation Officer is required.

VIII. PUBLIC NOTICE:

Upon publication of the public notice, a public comment period shall begin on the date of publication and last for at least 30 days thereafter. During this period, any interested persons may submit written comments on the draft permit modification and may request a public hearing to clarify issues involved in the permit decision at this Office's address on the first page of the statement of basis. A request for a public hearing shall be in writing and shall state the nature of the issues proposed to be raised in the hearing.

Public notice published in:

Local newspaper of general circulation

Office of Environmental Services Public Notice Mailing List

For additional information, contact:

Mr. Eura DeHart Permits Division Department of Environmental Quality Office of Environmental Services P. O. Box 4313 Baton Rouge, Louisiana 70821-4313

LA0038709; A119807; PER20070002

Page 5

IX. PROPOSED PERMIT LIMITS:

The reporting requirements of the previous permit for cadmium and lead were removed from the permit as it was determined a water quality limit was not needed.

Final Effluent Limits:

OUTFALL 001

Final limits shall become effective on the effective date of the permit and expire on the expiration date of the permit.

Effluent Characteristic	Monthly Avg. (lbs./day)	Monthly Avg.	Weekly Avg.	Basis
CBOD₅	92	10 mg/l	15 mg/l	Limits are set in accordance with the Louisiana Water Quality Management Plan, Houston River Wastershed TMDL for Biological Oxygen-Demanding Substances, and the previous permit
TSS	138	15 mg/l	23 mg/l	Since there is no numeric water quality criterion for TSS, and in accordance with the current Water Quality Management Plan, the TSS effluent limitations shall be based on a case-by-case evaluation of the treatment technology being utilized at a facility. Therefore, a Technology Based Limit has been established through Best Professional Judgement for the type of treatment technology utilized at this facility.
Ammonia- Nitrogen	18	2 mg/l	4 mg/l	Limits are set in accordance with the Louisiana Water Quality Management Plan, Houston River Wastershed TMDL for Biological Oxygen- Demanding Substances, and the previous permit
Dissolved Oxygen**		5.0 mg/l	N/A	Louisiana Water Quality Management Plan and the Houston River Wastershed TMDL for Biological Oxygen- Demanding Substances

LA0038709; AL19807; PER20070002

Page 6

"This Dissolved Oxygen limit is the lowest allowable average of daily discharges over a calendar month. When monitoring is conducted, the Dissolved Oxygen shall be analyzed immediately, as per 40 CFR 136.3.

Priority Pollutants

Effluent Characteristic	Monthly Avg. (Ibs./day)	Daily Maximum (lbs./day)	Basis
Total Copper	0.21	0.50	Water Quality Screen indicated no need for a WQBL; however, the limit will remain in the permit due to prior noncompliance record.*

^{*}The limitation for total copper has been set at the calculated water quality based limit. The change of the limitation from the previous permit represents a change in the calculated water quality based limit.

Other Effluent Limitations:

1) Fecal Coliform

The discharge from this facility is into a water body which has a designated use of Primary Contact Recreation. According to LAC 33:IX.1113.C.5, the fecal coliform standards for this water body are 200/100 ml and 400/100 ml. Therefore, the limits of 200/100 ml (Monthly Average) and 400/100 ml (Weekly Average) are proposed as Fecal Coliform limits in the permit. These limits are being proposed through Best Professional Judgement in order to ensure that the water body standards are not exceeded, and due to the fact that existing facilities have demonstrated an ability to comply with these limitations using present available technology.

2) pH

According to LAC 33:IX.3705.A.1., POTW's must treat to at least secondary levels. Therefore, in accordance with LAC 33:IX.5905.C, the pH shall not be less than 6.0 standard units nor greater than 9.0 standard units at any time.

3) Solids and Foam

There shall be no discharge of floating solids or visible foam in other than trace amounts in accordance with LAC 33:IX.1113.B.7.

4) Toxicity Characteristics

In accordance with EPA's Region 6 Post-Third Round Toxics Strategy, permits issued to treatment works treating domestic wastewater with a flow (design or expected) greater

LA0038709: A119807: PER20070002

Page 7

than or equal to 1 MGD shall require biomonitoring at some frequency for the life of the permit or where available data show reasonable potential to cause lethality, the permit shall require a whole effluent toxicity (WET) limit (*Permitting Guidance Document for Implementing Louisiana Surface Water Quality Standards*, August 13, 2007 VERSION 5).

Whole effluent biomonitoring is the most direct measure of potential toxicity which incorporates the effects of synergism of the effluent components and receiving stream water quality characteristics. Biomonitoring of the effluent is, therefore, required as a condition of this permit to assess potential toxicity. LAC 33:IX.1121.B.3. provides for the use of biomonitoring to monitor the effluent for protection of State waters. The biomonitoring procedures stipulated as a condition of this permit are as follows:

The permittee shall submit the results of any biomonitoring testings performed in accordance with the LPDES Permit No. LA0038709, **Biomonitoring Section** for the organisms indicated below.

TOXICITY TESTS

FREQUENCY

Chronic static renewal 7-day survival & reproduction test using <u>Ceriodaphnia dubia</u> (Method 1002.0)

1/quarter

Chronic static renewal 7-day survival & growth test using fathead minnow (Pimephales promelas) (Method 1000.0)

1/quarter

<u>Dilution Series</u> - The permit requires five (5) dilutions in addition to the control (0% effluent) to be used in the toxicity tests. These additional concentrations shall be 28%, 38%, 50%, 67%, and 89%. The low-flow effluent concentration (critical low-flow dilution) is defined as 89% effluent. The critical dilution is calculated in Appendix B-1 of this fact sheet. Results of all dilutions shall be documented in a full report according to the test method publication mentioned in the **Biomonitoring Section** under Whole Effluent Toxicity. This full report shall be submitted to the Office of Environmental Compliance as contained in the Reporting Paragraph located in the **Biomonitoring Section** of the permit.

The permit may be reopened to require effluent limits, additional testing, and/or other appropriate actions to address toxicity if biomonitoring data show actual or potential ambient toxicity to be the result of the permittee's discharge to the receiving stream or water body. Modification or revocation of the permit is subject to the provisions of LAC 33:IX.2383. Accelerated or intensified toxicity testing may be required in accordance with Section 308 of the Clean Water Act.

LA0038709: AI19807: PER20070002

Page 8

X. PREVIOUS PERMITS:

LPDES Permit No. LA0038709: Issued: March 1, 2001 Expired: February 28, 2006

Effluent Characteristic	Discharge Limit	tations	Monitoring Requirements			
	Daily Avg.	Daily Max.	<u>Measurement</u>	Sample		
			Frequency	<u>Type</u>		
Flow	Report	Report	Continuous	Recorder		
CBOD ₅	10 mg/l	15 mg/l	2/week	6-Hour Composite		
TSS	15 mg/l	23 mg/l	2/week	6-Hour Composite		
Ammonia-Nitrogen	2 mg/l	4 mg/l	2/week	6-Hour Composite		
Fecal Coliform Colonies	200	400	2/week	Grab		
Copper	0.22 lbs/day	0.52 lbs/day	1/quarter	24-Hour Composite		
Cadmium	Report .	Report	1/6 months	24-Hour Composite		
Lead	Report	Report	1/6 months	24-Hour Compos		
Biomonitoring						
Pimephales promelas	Report	Report	1/quarter	24-Hour Composite		
Ceriodaphnia dubia	Report	Report	1/quarter	24-Hour Composite		

The permit contains biomonitoring.

The permit contains pollution prevention language.

The permit contains pretreatment language.

XI. <u>ENFORCEMENT AND SURVEILLANCE ACTIONS:</u>

A) Inspections

A review of the files indicates the most recent inspection was conducted on November 29, 2007for this facility.

Inspector's Observations:

A compliance evaluation inspection was conducted with the following noted:

- DMR review from 10/06 10/07 revealed several excursions in 03/07 05/07 sample period
- Loading calculation check on NH3 for Aug. '07
- Permit renewal application deemed complete on 6/14/07
- 24 hour notification was not done on 03-05/07 for copper exceedence
- NIST thermometer for sample refrigerator last calibrated on 6/15/07
- Flow meter last calibrated on 4/4/07 Primary 9" parshall flume
- Flow proportioning of 6-hour and 24-hour composite sampling is not conducted properly. (Recommend composite sampler be used during sampling events)

LA0038709; A119807: PER20070002

Page 9

1/7/08 Supplemental

Upon further review of information obtained during the course of the 11/29/07 inspection, the following areas of concern are noted:

- The operators daily log indicated that the facility is not recording the daily flow for a 24 hr period and is rounding the effluent flow rate (MGD)
- The facility did not retest the TLP3B test when a failing result was reported during the 03-05/07 sample period.

B) Compliance and/or Administrative Orders

A review of the files indicates there are no recent enforcement actions administered against this facility.

C) DMR Review

A review of the discharge monitoring reports for the period beginning May 1, 2005 through November 30, 2007 has revealed the following violations:

Parameter	Outfall	Period of Excursion	Permit Limit	Reported Quantity
Total Copper (Monthly Avg.)	001	December 2005 - February 2006	0.22 lbs/day	0.799 lbs/day
Total Copper (Daily Max.)	001	December 2005 - February 2006	0.52 lbs/day	0.799 lbs/day
Total Copper (Monthly Avg.)	001	March - May 2006	0.22 lbs/day	0.659 lbs/day
Total Copper (Daily Max.)	001	March - May 2006	0.52 lbs/day	0.659 lbs/day

XII. ADDITIONAL INFORMATION:

The Department of Environmental Quality reserves the right to impose more stringent discharge limitations and/or additional restrictions in the future to maintain the water quality integrity and the designated uses of the receiving water bodies based upon additional water quality studies and/or TMDLs. The DEQ also reserves the right to modify or revoke and reissue this permit based upon any changes to established TMDLs for this discharge, or to accommodate for pollutant trading provisions in approved TMDL watersheds as requested by the permittee and/or as necessary to achieve compliance with water quality standards. Therefore, prior to upgrading or expanding this facility, the permittee should contact the Department to determine the status of the work being done to establish future effluent limitations and additional permit conditions.

Effluent loadings are calculated using the following example:

BOD: 8.34 gal/lb x 1.1 MGD x 10 mg/l = 92 lb/day

At present, the Monitoring Requirements, Sample Types, and Frequency of Sampling as shown in the permit are standard for facilities of flows between 1.0 MGD and 5.0 MGD.

Effluent Characteristics

Measurement Sample
Frequency Type

Flow
Continuous Recorder
Total Suspended Solids

Measurement Sample
Frequency Type
Continuous Recorder
6 Hr. Composite

LA0038709; A119807; PER20070002

Page 10

BOD₅		2/week	6 Hr. Composite
	nia-Nitrogen	2/week	6 Hr. Composite
Dissolv	ed Oxygen	2/week	Grab
Fecal C	oliform Bacteria	2/week	Grab
Total C	opper	1/quarter	24 Hr. Composite
Biomon	itoring		
	Ceriodaphnia dubia (Method 1002.0)	1/quarter	24 Hr. Composite
	Pimephales promelas (Method 1000.0)	1/quarter	24 Hr. Composite
рН		2/week	Grab

Pretreatment Requirements

Based upon consultation with LDEQ pretreatment personnel, general pretreatment language will be used due to the lack of either an approved or required pretreatment program. (See attached Pretreatment Evaluation and Recommendation)

Pollution Prevention Requirements

The permittee shall institute or continue programs directed towards pollution prevention. The permittee shall institute or continue programs to improve the operating efficiency and extend the useful life of the facility. The permittee will complete an annual Environmental Audit Report <u>each year</u> for the life of this permit according to the schedule below. The permittee will accomplish this requirement by completing an Environmental Audit Form which has been attached to the permit. All other requirements of the Municipal Wastewater Pollution Prevention Program are contained in Part II of the permit.

The audit evaluation period is as follows:

Audit Period	Audit Period	Audit Report
Begins	Ends	Completion Date
Effective Date of Permit	12 Months from Audit Period Beginning Date	3 Months from Audit Period Ending Date

Stormwater Discharges

Because the design flow of the DeQuincy Wastewater Treatment Facility is equal to or greater than 1.0 MGD and in accordance with LAC 33:1X.2511.B.14.i, the facility may contain storm water discharges associated with industrial activity. Therefore, in accordance with LAC 33:1X.2511.A.1.b, specific requirements addressing stormwater discharges will be included in the discharge permit.

XIII <u>TENTATIVE DETERMINATION:</u>

On the basis of preliminary staff review, the Department of Environmental Quality has made a tentative determination to reissue a permit for the discharge described in this Statement of Basis.

LA0038709: A119807: PER20070002

Page 11

XIV REFERENCES:

Louisiana Water Quality Management Plan / Continuing Planning Process, Vol. 8, "Wasteload Allocations / Total Maximum Daily Loads and Effluent Limitations Policy," Louisiana Department of Environmental Quality, 2005.

Louisiana Water Quality Management Plan / Continuing Planning Process, Vol. 5, "Water Quality Inventory Section 305(b) Report," Louisiana Department of Environmental Quality, 1998.

<u>Louisiana Administrative Code, Title 33 - Environmental Quality, Part IX - Water Quality Regulations. Chapter 11 - "Louisiana Surface Water Quality Standards"</u>, Louisiana Department of Environmental Quality, 2004.

<u>Louisiana Administrative Code, Title 33 - Environmental Quality, Part IX - Water Quality Regulations, Subpart 2 - "The LPDES Program"</u>, Louisiana Department of Environmental Quality, 2004.

<u>Low-Flow Characteristics of Louisiana Streams</u>, Water Resources Technical Report No. 22. United States Department of the Interior, Geological Survey, 1980.

Index to Surface Water Data in Louisiana. Water Resources Basic Records Report No. 17, United States Department of the Interior, Geological Survey, 1989.

<u>LPDES Permit Application to Discharge Wastewater</u>, City of DeQuincy, DeQuincy Wastewater Treatment Facility, June 14, 2007.

APPENDIX I

Numeric Toxic Limits: LDEQ has reviewed and evaluated the effluent analyses submitted by the permittee on June 14, 2007 and reported on DMRs from March 2005 to November 2007, and examined the following pollutants that are regulated by LAC 33:IX.1113.C.6. in accordance with the implementation procedures outlined under the <u>Permitting Guidance Document for Implementing Louisiana Surface Water Quality Standards, August 13, 2007. Please see Appendix B-1, Water Quality Screen Spreadsheet.</u>

Pollutant	Ce ¹	Ce x 2.13 ²	Water Quality Based Limit ³	Drinking Water Source	Permit Limit ?
Cadmium	0.003 lbs/day	0.0068 lbs/day	0.0362 lbs/day		No
Copper	0.08 lbs/day	0.170 lbs/day	0.2104 lbs/day		No
Zinc	66 µg/L	140.58 µg/L	1.4937 lbs/day		No
Lead	0.013 lbs/day	0.0277 lbs/day	0.1016 lbs/day	****	No

- Metals concentration results were presented as total metals in lab analysis submitted by the permittee.
- 2/ For the reported effluent concentrations (Ce) it is estimated that 95% of the concentrations of chemicals taken over time will be 2.13 times the Ce or less.
- 3/ The water quality based limit is the maximum allowable instream concentration for that pollutant to be in compliance with water quality standards. Louisiana Water Quality Criteria for metals are hardness dependent, and expressed as dissolved metals. The water quality based limit is calculated with a conversion for metals limits expressed as total metals.

The following steps were used in evaluating the potential toxicity of the analyzed pollutants (see Appendix B-1):

i. An evaluation of the applicability of the effluent data.

Results of the PPS were entered and compared to EPA's Minimum Quantification Levels (MQL's) to determine the potential presence of the respective toxic pollutant. Those pollutants with reported laboratory Method Detection Levels (MDL's) which exceed their respective EPA MQL's are determined to be reasonably present in the effluent and an evaluation of their potential toxicity is determined. Those pollutants with MDLs less than the MQL are determined to be not potentially present in the effluent and eliminated from further evaluation. Data for cadmium, copper, and lead submitted on DMRs were also reviewed from March 2005 to November 2007. This data was also compared to the water quality based limit.

ii. Calculation of permit limits based on applicable water quality standards.

Applicable water quality criteria are listed in the Appendix B-1 in Columns 12-14. These

Appendix 1 Page 2

values were used to calculate the Waste Load Allocations (WLAs) for each of the toxic pollutants. The WLA is the maximum allowable concentration of a pollutant necessary to meet the respective water quality criteria. The WLAs are calculated as described in the State's Permitting Guidance Document for Implementing Louisiana Surface Water Quality Standards, dated August 13, 2007, as follows (Zinc is used as the example pollutant for the following calculations):

Complete Mix Balance Model for Waste Load Allocation

Qe = plant effluent, MGD = 1.1

Qr = critical flow of receiving stream, **0.20 cfs**Fs = MZ, ZID flow fraction, LAC 33:IX.1115.D.7

and 8 (MZ = 1, and ZID = 0.1)

Cr = numerical criteria value from LAC 33:IX.1113, Table 1

Cu = ambient instream concentration for pollutant. In the absence of accurate

supporting data, assume Cu = 0

WLA = concentration for pollutant at end-of-pipe based on aquatic life and

human health numerical criteria (site specific dilution type)

LTA = long term average, units same as WLA

WQBL = effluent water quality based limit.

Dilution factor
$$= \frac{Qe}{(QrFs + Qe)}$$

Dilution factor (acute) $= \frac{1.1}{(0.20)(0.6463)(0.1) + 1.1}$
 $= 0.988$

Dilution factor (chronic) $= \frac{1.1}{(0.20)(0.6463)(1.0) + 1.1}$
 $= 0.895$

WLA = (Cr/Dilution factor) - (FsQrCu/Qe)

iii. Conversion of dissolved metals criteria for aquatic life to total metals.

Metals criteria for aquatic life protection are based on dissolved metals concentrations and hardness values averaged from data compilations contained in the Louisiana Water Quality Data Summary. A dissolved to total metal conversion will be implemented. Hardness and TSS are a function of the conversion. This involves determining a linear partition coefficient for the metal of concern and using this to determine the fraction of metal dissolved, so that the dissolved metal ambient criteria may be translated to a total effluent limit. The average hardness value used for the analysis is 119.0 mg/l CaCO3 (USGS data). The 15th percentile TSS value is 4.0 mg/l. The formula for converting dissolved metals to total metals for streams and lakes are provided below.

 K_p = Linear partition coefficient K_{po} = found in Table A below α = found in Table A below

TSS = total suspended solids concentration found in receiving stream or

approximation thereof (nearest most representative site), lowest 15th

percentile, units in mg/l

 C_0/C_T = Fraction of metal dissolved

Appendix I Page 3

$$K_{p} = K_{po} \times TSS^{\alpha}$$

$$K_{p} = (1.25 \times 10^{6}) \times 4.0^{(-0.7)}$$
then,
$$\frac{C_{D}}{C_{T}} = \frac{1}{1 + (K_{P})(TSS)(10^{-6})}$$

$$\frac{C_{D}}{C_{T}} = \frac{1}{1 + (473,661.43)(4.0)(10^{-6})}$$

$$= 0.35$$
therefore,

Total Metal =
$$\frac{Cr}{(C_D/C_T)}$$

TABLE A

LINEAR PARTITION COEFFICIENTS FOR PRIORITY METALS IN STREAMS AND LAKES

(Delos et. al, 1984) (*1)

METAL	STRE	AMS	LAKES			
	K _{po}	α ·	K _{po}	α		
Arsenic	0.48 x 10 ⁶	-0.73	0.48 x 10 ⁶	-0.73		
Cadmium	4.00 x 10 ⁶	-1.13	3.52 x 10 ⁶	-0.92		
Chromium III (*2)	3.36 x 10 ⁶	-0.93	2.17 x 10 ⁶	-0.27		
Copper	1.04 x 10 ⁶	-0.74	2.85 x 10 ⁶	-0.9		
Lead	2.80 x 10 ⁶	-0.8	2.04 x 10 ⁶	-0.53		
Mercury	2.90 x 10 ⁶	-1.14	1.97 x 10 ⁶	-1,17		
Nickel	0.49 x 10 ⁶	-0.57	2.21 x 10 ⁶	-0.76		
Zinc	1.25 x 10 ⁶	-0.7	3.34 x 10 ⁶	-0.68		

- (*1) Delos, C. G., W. L. Richardson, J. V. DePinto, R. B. Ambrose, P. W. Rogers, K. Rygwelski, J. P. St. John, W. J. Shaughnessey, T. A. Faha, W. N. Christie. Technical Guidance for performing Waste Load Allocations, Book II: Streams and Rivers. Chapter 3: Toxic Substances, for the U. S. Environmental Protection Agency. (EPA-440/4-84-022).
- (*2) Linear partition coefficients shall not apply to the Chromium VI numerical criterion. The approved analytical method for Chromium VI measures only the dissolved form. Therefore, permit limits for Chromium VI shall be expressed in the dissolved form. See 40 CFR 122.45(c)(3).

Appendix I Page 4

```
WLA a,c,h = (Cr/Dilution factor) - (FsQrCu/Qe)
```

```
WLA <sub>acute</sub> = (383.27/0.988) - [(0.1)(0.872)(0)/1.4] = 387.93
```

WLA $_{chronic}$ = (349.98/0.895) - [(1.0)(0.872)(0)/1.4] = 391.04 iv. Calculation of Long Term Averages (LTA's) and Permit Limits.

Comparison of the reported effluent data (converted to the 95th percentile) to the calculated effluent limitations. Long term averages are listed in the Appendix B-1 in Columns 15-17.

Long term averages are calculated for each WLA (based on aquatic and human health criteria). The LTA's are calculated as follows:

LTA_a = WLA_a
$$\times$$
 0.32
LTA_c = WLA_c \times 0.53
LTA_h = WLA_h

$$LTA_{acute} = 387.93 \times 0.32 = 124.14$$

 $LTA_{chronic} = 391.04 \times 0.53 = 207.25$

A comparison of each LTA is made and the lowest (most restrictive) is selected to calculate the effluent limitations. The most limiting LTA is listed in Appendix B-1, Column 18.

Calculation of permit limits if aquatic life LTA is more limiting:

```
Daily Average = Min(LTA_a, LTA_c) \times 1.31
Daily Maximum = Min(LTA_a, LTA_c) \times 3.11
```

Daily Average = $124.14 \times 1.31 = 162.62 \mu g/l$ Daily Maximum = $124.14 \times 3.11 = 386.08 \mu g/l$

If human health LTA is more limiting:

Daily Average = LTA_h Daily Maximum = $LTA_h \times 2.38$

The resulting allowable effluent concentration is converted to a mass value using the following formula:

lbs/day =
$$(0.16262 \text{ mg/l}) \times 8.34 \times 1.1 \text{ MGD}$$

= 1.49

Comparison of the reported effluent data (converted to 95th percentile) is made to the calculated effluent limitations. Water Quality Based limits are listed in Appendix B-1, Columns 19-22.

In accordance with the State of Louisiana's implementation procedures, the reported effluent concentration is compared to the calculated daily average concentration. If the effluent concentration is greater than the calculated daily average concentration, then a reasonable potential exists and an effluent limitation for the pollutant of concern is imposed in the permit. (Please refer to Appendix B-1 for the calculated daily average concentration listed in Column 19 and the effluent concentration listed in Column 3.)

Appendix I Page 5

The discharge is considered to pose a reasonable potential to cause a water quality excursion if the estimated 95th percentile of a pollutant in the effluent will result in an instream waste concentration, which is above the applicable State water quality criterion. The 95th percentile of possible effluent concentrations are estimated as follows:

$$C_{95} = C_{mean}^* \exp(1.645^* \sigma - 0.5^* \sigma^2)$$

where: 1.645 = normal distribution factor at 95th percentile

$$\sigma^2 = \ln(CV^2 + 1)$$
if CV is assumed = 0.6,
 $\sigma^2 = .307$

The ratio of the estimated 95th percentile value to the mean (C_{95}/C_{mean}) is calculated :

$$C_{95}/C_{mean} = 2.13$$

Based upon review of the permittee's effluent data, there are no pollutant(s) present or potentially present in the effluent discharge in such concentrations which would cause an exceedance of Louisiana's Water Quality Standards. However, a limit for cooper will remain in the permit. A summary of the evaluation of the permittee's effluent analysis of the toxic pollutants is listed in Appendix B-1. As per LAC 33:(X.2709.F.1, all pollutants limited in permits shall have limitations, standards, or prohibitions expressed in terms of mass. Consequently, water quality-based limitations as seen in the permit are expressed in terms of mass.

wqsmedn wk4	Date 03 04 Ap		Appendix B-	Appendix B-1				
Developer Bruce Fielding	Time	10 40 VVI	1.40038200	LA0078709 , AI 19807				
Software Lotus 4.0 Revision date: 02/14/05			12/0/02/07/07	, 241 12607				
Revision date. 02/14/01	Water Quali	tu Caraun C	ar Circuit Date	uincy WWTF				
Input variables:	water Quan	iy Acreen i	or Chy or Dec	ame,				
Receiving Water Characteristics:			Dilution:		Toxicity Dilution Series			
recerring water Characteristics.			ZID F5 €	0.1	Biomonitoring dilution:		0.894847	
Receiving Water Name=	Buxton Creel				Dilution Series Factor		0.75	
Critical flow (Qr) efs=	0.2		MZ Fs =	1	Dranen seres rucio		0.75	
Harm mean/avg tidal efs=	0,2		Critical Qr (MGD)=	0 12926			Percent Effluent	
Drinking Water=1 HHNPCR=2			Harm, Mean (MGD)=	0.12926	Dilution No. 1		89 485%	
Marine, I=y, U=n			ZID Dilution =	0.988386	Dilution No. 2		67 1135%	
Rec Water Hardness*	119		MZ Dilution =	0.894847	Dilution No. 3		50 3352%	
Rec. Water TSS=	4		HHne Dilution#	0.894847	Dilution No. 4		37.7514%	
Fisch/Specific=1,Stream=0			HHc Dilution=	0.894847	Dilution No. 5		28.3135%	
Diffuser Ratio=			ZID Upstream =	0.011751				
			MZ Upstream =	0.117509	Partition Coefficients; Dissolved	>Total		
Effluent Characteristics:			MZhhac Upstream=	0.117509				
Pennittee=	City of DeQu	tiney WW	TF .		METALS	FW		
Pennii Number=	LA0038709		•		Total Atsenic	1,697907		
Facility flow (Qef),MGD=	1.1		MZhhc Upstream=	0.117509	Total Cadmium	4,340352		
			ZID Hardness=		Chromium III	4 702401		
Outfall Number =	001		MZ Hardness=		Chromiun VI	1		
Eff, data, 2=lbs/day			ZID TSS=		Total Copper	2 491313		
MQL 2=lbs day			MZ TSS=		Total Lead	4 094622		
Effluent Hardness=	N/A		Multiphers:		Total Mercury	3 388414		
Effuent TSS-	N/A		WLAa> LTAa	0.32	Total Nickel	1,889369		
WQBL ind 0=v, 1≈n			WLAc> LTAc	0.53	Total Zinc	2.894646		
Acute:Chr. ratio 0=n, 1=y			LTA a.c>WOBL avg	1.31				
Aquatic acute only I=y,0=n			LTA a.c>WQBL max	3,11	Aquatic Life, Dissolved			
			LTA h> WQBL max	2.38	Metal Criteria, ug/l.			
Page Numbering/Labeling			WQBL-limit/report	2.13	METALS	ACUTE	CHRONIC	
Appendix	Appendix B	-1	WLA Fraction	1	Arsenic	339.8	150	
Page Numbers 1=y, 0=n	1		WQBL Fraction	1	Cadmium	38 40101	1.172479	
Input Page # 1=y, 0=n	1				Chromium III	632,7587	205,2604	
			Conversions:		Chromium VI	15.712	10.582	
FischenSite Specific inputs:			ug/L>lbs/day Qef	0,009174	Copper	21.70772	14.2526	
Pipe=1.Canal=2.Specific=3			ug/L>lbs/day Oeo	0	Lead	78.00709	3.039824	
Pipe width, feet			ug/L>lbs/day Qr	0,001668	Mercury	1.734	0.012	
ZID plume dist., feet			lbs/day>ug/L Qeo	109.0037	Nickel	1639 811	182,1142	
MZ plume dist , feet			lbs/day>ug/L Qef	109.0037 1	Zinc	132,6224	121,1043	
HHnc plume dist., feet			diss>tot 1=y0=n	1	City Specific & Julianian	\'alunc:		
HHc plume dist., feet			Cu diss->tot1=y0=n cfs>MGD	0.6463	Site Specific Multiplier ' CV =	· macs,		
Fischer/site specific dilutions:			C13>p1010	0.0403	N =		•••	
) Dilution =			Receiving Stream;		WLAa> LTAa			
F/specific MZ Dilution =			Default Hardness≠	25	WLAc> LTAc			
F/specific HHnc Dilution=			Default TSS=	10	LTA a.c->WOBL avg			
F/specific IIHe Dilution=	•••		99 Crit 1∗y, 0=n	1	LTA a.c>WQBL max			
					LTA h> WQBL max			

Appendix B-1 City of DeQuincy WWTF LAG038709 ; AL 19807

(*1)	(*2)	(*3)	(1-1)	(*5)	(*6)	(*7)	(*8)	(-9)	(*10)	(*11)
Toxic		Effluent	Effluent		Effluent	95th %	. ,	cal Criteria	(10)	18H (*11)
Parameters	Instream	Tech	/l'ech		1=No 95%	estimate	Acute	Chronic	HILISTON	Carcinoge
	Cone	(Avg)			0=95 %	Non-Tech	FW	FW	HIMDW	Indicator
	ug/L	ug/L	ug/L	ug/L		ngd.	սց/լ.	ug'l.	սբ/է,	"C"
NONCONVENTIONAL	•	•					ц.,.	uf i	սը/ւ.	C
Total Phenols (4AAP)				5			700	350	50	
3-Chlorophenol				10				20	20	
4-Chlorophenol				10			383	192		
2.3-Dichlorophenol				10						
2.5-Dichlorophenol				10						
2.6-Dichlorophenol				10						
3,4-Dichtorophenol				10						
2.4-Dichlorophenocy-										
acctic acid (2,4-D)										
2-(2.4,5-Trichlorophen-										
oxy) propionic acid										
(2.4.5-TP, Silvex)										
MÉTALS AND CYANIDE										
Total Arsenic				10			576,9487	254,686		
Total Cadmium				1			166,6739	5.088969		
Chromium III				10			2975.485	965.2166		
Chromium VI				10			15.712	10,582		
Total Copper				10			54.08075	35.50768		
Total Lead				5			366,2138	14.27083		
Total Mercury				0.2			5.87551	0.040661		
Total Nickel				40			3098.208	344.0809		
Total Zinc		66		20	Ü	140.58	383,8948	350.5541		
Total Cyanide				20			45,9	5.4	12844	
DIONIN										
DIONIN 2,3,7,8 TCDD; dioxin										
2.5,7,6 TC1515; GIGMIN				1.0E-05					7.2E-07	C
VOLATILE COMPOUNDS										
Benzene				10			2249	1125	12.5	c
Bromoform				10			2930	1465	34.7	C
Bromodichloromethane				10					3.3	C
Carbon Tetrachloride				10			2730	1365	1.2	C
Chloroform				10			2890	1445	70	C
Dibromochloromethane				10					5.08	C
1,2-Dichloroethane				10			11800	5900	6.8	C
1.1-Dichloroethylene				10			1160	580	0.58	C
1.3-Dichloropropylene				10			606	303	162,79	
Ethylbenzene				10			3200	1600	8100	
Methyl Chloride Methylene Chloride				50			55000	27500		
1.1.2.2-Tetrachloro-				20			19300	9650	87	C
ethane				10						_
				10			932	466	1.8	C

Appendix B-1 City of DeQuincy WWTF 1,A0058709; Al 19807

(*1)	(*12)	(*13)	(*14)	(*15)	(*16)	(*17)	(*18)	(*19)	(*20)	(*21)	(*22)	(*23)
Toxic	WLAa	WLAc	WLAb	LTAa	MAc	1.TAh	Limiting	WQBL	WQBL	WQB1.	WQBL	Need
Parameters -	Acute	Chronic	HHNDW	Acute	Chrome	HHNDW	A.C.HH	Avg	Max	Avg	Max	w QBI
								001	001	001	001	
	սք/1,	ug/L	սց/Լ	ug/).	սք Դ.	սջքՆ	ug/l,	ug l.	ug/L	lbs day	lbs/day	
NONCONVENTIONAL						-		•	•	•	•	
Total Phenols (4AAP)	708.2256	391.1282	55.87545	226 6322	207,2979	55,87545	55,87545	55.87545	132 9836	0,512601	1,219991	no
3-Chlorophenol				***		***						no
4-Chlorophenol	387.5006	214,5617		124,0002	113.7177	•••	113.7177	148 9702	353.6621	1,366653	3.244496	no
2.3-Dichlorophenol			•••		***	•••	•••	•••				110
2,5-Dichlorophenol		***		***					***		•••	no
2.6-Dichlorophenol							**-	***				no
3.4-Dichtorophenol		***	•••							***		110
2,4-Dichtorophenocy-												
acetic acid (2,4-D)												no
2-(2,4,5-Trichlorophen-												,,,,
oxy) propionic acid												
(2,4,5-TP, Silvex)	***									•••	•••	no
(2.5,5-11, 50000)							•			•		110
METALS AND CYANIDE												
Total Arsenic	583.7284	284.6139		186,7931	150,8454		150,8454	197.6075	169.1292	1,812851	4,303791	no
Total Cadmium	168.6324	5.686969	•••	55.96238	3.014094		3.014094	3 948463	9.373831	0.036223	0.085996	no
Chromium III	3010.45	1078.638		963,3439	571.6783		571.6783	748.8986	1777.92	6.870396	16,31063	no
Chromium VI	15.89663	11.82548	4	5,086922	6,267505		5.086922	6.663867	15.82033	0.061134	0 145136	no
Total Copper	54.71624	39.68016	***	17.5092	21.03048	***	17.5092	22.93705	54.45361	0.210424	0.499557	no
Total Lead	370 5172	15.94778		118.5655	8.452323	•••	8.452323	11.07254	26.28672	0.10158	0.241154	no
Total Mercury	5.944552	0.045439	•••	1,902257	0.024083		0.024083	0.031548	0.074897	0.000289	0.000687	110
Total Nickel	3134.615	384,5135	•••	1003.077	203.7922		203,7922	266,9677	633.7936	2,449162	5,814423	no
Total Zinc	388.4059	391.7474		124.2899	207.6261		124.2899	162.8197	386.5415	1.493708	3,546132	no
Total Cyanide	46 43937	6.034549	14353.29	14 8606	3 198311	14353,29	3 198311	4,189787	9 946747	0.038437	0.091251	no
•												
DIOXIN												
2,3,7,8 TCDD; dioxin	y		8.05E-07			8.05E-07	8 05E-07	8.05E-07	1.91E-06	7.3811-09	1,76E-08	110
VOLATILE COMPOUNDS												
Benzene	2275.428	1257,198	13.96886	728.1369	666.3148	13.96886	13.96886	13.96886	33,2459	0.12815	0.304998	no
Bromoform	2964.43	1637.151	38.77757	948.6177	867.6899	38.77757	38.77757	38.77757	92.29061	0.355745	0.846674	no
Bromodichloromethane			3,68778			3.68778	3,68778	3.68778	8,776916	0.033832	0.080519	กอ
Carbon Tetrachloride	2762.08	1525.4	1.341011	883.8656	808.462	1.341011	1.341011	1,341011	3,191606	0.012302	0.02928	no
Chloroform	2923. 96	1614.801	78.22564	935.6672	855.8443	78.22564	78,22564	78.22564	186,177	0.717642	1,707988	nυ
Dibromochloromethane			5.676946	•••		5.676946	5,676946	5,676946	13.51113	0.05208	0.123951	no
1,2-Dichloroethane	11938.66	6593,304	7,599062	3820 371	3494.451	7.599062	7.599062	7,599062	18.08577	0.069714	0.165919	no
1,1-Dichloroethylene	1173,631	648.1553	0.648155	375.5619	343,5223	0.648155	0.048155	0.648155	1.54261	0.005946	0.014152	no
1,3-Dichloropropylene	613.1211	338.6053	181.9193	196,1987	179.4608	181,9193	179,4608	235.0936	558.123	2,156749	5,120221	nο
Ethylbenzene	3237.603	1788.015	9051,824	1036 033	947.6477	9051,824	947 6477	1241,418	2947 184	11 38877	27 03747	no
Methyl Chloride	55646.3	30731.5		17806.82	16287,7		16287.7	21336.88	50654.73	195,7445	464,7065	no
Methylene Chloride	19526,79	10783,96	97.22329	6248.574	5715,5	97.22329	97.22329	97.22329	231.3914	0 891926	2.122785	no
1,1,2,2-Tetrachloro-												
ethane	942.9518	530,7592	2.011516	301 7446	276.0024	2.011516	2,011516	2,011516	4,787409	0.018454	0 04392	nø

Appendix B-1 Cny of DeQuincy WWFF LA0038709 ; AI 19807

(*1) Toxic	(*2) Cu l	(*3) Effluent	(*4) Effluent	(*5) MQL	(*6) Effluent	(*7) 95th %	(*8) Numerica	(*9) d Criteria	(*10)	(*11) HH
Parameters	Instream	/Tech	/Tech		I=No 95%	estimate	Acute		ннири	Caremogen
	Conc.	(Avg)	(Max)		0=95 %	Non-Tech	FW	FW'		Indicator
	սբԴ.	սը/Լ	սբվ.	ugʻl.		սը.1,	սը (Լ	ug/L	ng/L	"C"
VOLATILE COMPOUNDS (cont'd)									
Tetrachloroethylene				10			1290	645	2.5	C
Toluene				10			1270	635	46200	
1,1,1 Frichtoroethane				10			5280	2640		
1, 1, 2-1 richlosoethane				10			1800	900	6.9	C
Trichloroethylene				10			3900	1950	21	C
Vinyl Chloride				10					35.8	C
ACID COMPOUNDS										
2-Chlorophenol				10			258	129	126.4	
2,4-Dichlorophenol				10			202	101	232.6	
BASE NEUTRAL COMPOU	NDS									
Benzidine				' 50			250	125	0.00017	C
Hexachlorobenzene				10					0 00025	c
Hexachlorabutadiene				01			5.1	1.02	0.11	C
PESTICIDES										
Aldrin				0.05			3		0.0004	C
Hexachlorocyclohexane										· ·
(gamma BHC, Lindane)				0.05			5.3	0.21	0,2	С
Chlordane				0.2			2.4	0.0043	0.00019	С
4,4'-DDT				0.1			1.1	0.001	0 00019	c
4.4'-DDE				0.1			52,5	10.5	0.00019	C
4.4DDD				0.1			0.03	0.006	0.00027	C
Dieldrin				0. i			0.2374	0.0557	0.00005	C
Endosulfan				0.1			0.22	0.056	0.64	
Endrin				0,1			0.0864	0.0375	0.26	
Heptachlor				0.05			0.52	0.0038	0 00007	C
Toxaphene				5			0,73	0.0002	0.00024	С
Other Parameters										
Fecal Col.(col/100ml)										
Chlorine							19	11		
Ammonia								4000		
Chlorides										
Sulfates TDS										
103					-					

Appendix B-1 Page 5 City of DeQuincy WWTF 1.A0038709 ; AI 19807

(*1)	(*12)	(*13)	(*14)	(*15)	(*16)	(*17)	(*18)	(*19)	(*20)	(*21)	(*22)	
Toxic	WLAa	WLAc	Wl.Ah	l,TAa	LTAc	LTAh	Limiting	WQBt.	WQBL	WQBL	WQBL	Need
Parameters	Acute	Chronic	HHNDW	Acute	Chronic	HHNDW	а,с,нн	Avg	Max	Avg		WOBI
								001	001	100	001	
	սք/Լ,	սց/Լ.	ug/l,	ug∕l.	ug/l,	սց/Լ.	ug/L	ug/l,	սց/1.	Ibs/day	lbs'day	
Tetrachloroethylene	1305,159	720,7934	2.793773	417,6508	382,0205	2,793773	2,793773	2.793773	6 649179	0.02563	0.061	no
Toluene	1784,924	709 6183	51628,97	411,1756	376 0977	51628,92	376,0977	193.688	1169,664	4.519919	10.7305	no
1,1,1-Trichloroethane	5342.045	2950,224		1709,454	1563.619		1563.619	2048,341	4862.854	18 79148	44 61182	no
1,1,2-Trichloroethane	1821,152	1005.758	7.710813	582 7685	533,0518	7.710813	7 710813	7.710813	18.35173	0.070739	0 168359	no
Trichloroethylene	3945,829	2179.143	23,46769	1262,665	1154 946	23,46769	23,16769	23 46769	55 8531	0,215293	0.512396	no
Vinyl Chloride	•••		40.00683	***		40.00683	40 00683	40.00683	95,21624	0.367023	0 873514	no
ACID COMPOUNDS												
2-Chlorophenol	261,0317	144.1587	141.2531	83.53016	76,4041	141.2531	76,4041	100.0894	237,6167	0.91822	2.179896	no
2,4-Dichtorophenol	204,3737	112.8684	259,9326	65.39958	59.82026	259.9326	59,82026	78.36454	186 041	0.718916	1,70674	กง
DACE APPERED AT COMMONIA	une											
BASE NEUTRAL COMPOUN	252,9377	139.6886	0.00019	20.01002	74.03498	0.00010	0.00010	0.00010	0.006153	1 2 1 5 44		
Benzidine		•		80.94007	44.VJ.H3	0.00019	0.00019	0,00019	0.000452	1.74E-06	4.15E-06	no
Hexachtorobenzene			0.000279		0.604125	0,000279	0.000279	0.000279	0.000665	2,561:-06	6.1E-06	រាប
Hexachlorabutadiene	5.15993	1.139859	0.122926	1.651177	0,604125	0,122926	0.122926	0.122926	0,292564	0.001128	0.002684	no
PESTICIDES												•
Aldrin	3.035253		0.000447	0.971281	•••	0.000447	0.000447	0.000447	0.001004	4.1E-06	9.76E-06	no .
Hexachlorocyclohexane												
(gamma BHC, Lindane)	5,36228	0.234677	0,223502	1,71593	0.124379	0,223502	0.124379	0.162936	0,386818	0.001495	0.003549	но
Chlordane	2.428202	0.004805	0 000212	0,777025	0.002547	0,000212	0 000212	0.000212	0 000505	1.951;-06	4.641:-06	no
4,4'-DDT	1.112926	0.001118	0.000212	0.356136	0.000592	0.000212	0.000212	0.000212	0.000505	1.95E-06	4 641:-06	no
4,4'-DDE	53.11692 0.030353	0.006705	0.000212	16,99742 0,009713	6.218938 0.003554	0.000212	0 000212	0.000212	0.000505	1.95E-06	4.64E-06	no
4,4'-DDD Dieldrin	0.24019	0.062245	5.59E-05	0.009713	0.03334	5.59E-05	5.59E-05	0.000302 5.5912-05	0.000718	2,77E-06 5,13E-07	6,59E-06 1,22E-06	по
Endosulfan	0.222585	0.062581	0.715206	0.070801	0.03299	0.715206	0.033168	0.04345	0.000133	0.000399	0.000946	no no
Endrin	0.222383	0.041907	0.290552	0.077973	0.02221	0.290552	0.02221	0.029096	0.069075	0.000347	0.000634	nο
Hemachlor	0.52611	0.004247	7.82E-05	0.168355	0.002251	7.82E-05	7.82E-05	7.82E-05	0.000186	7.18E-07	1.71E-06	
першення	0,02077	0.001217	7.022 05	0.100,00	*.00225	V.012 01	7,021, 42	7.021.03	0.000100	7.701, 01		110
Toxaphene	0.738578	0.000224	0.000268	0.236345	0.000118	0.000268	0.000118	0.000155	0.000368	1.42E-06	3,38E-06	no
Other Parameters:					•••				•			
Fecal Col (col/100ml)	19,22327	12.2926		6.151446	6.515078			8.058394	19,131	0.073928	0.175600	no
Chlorine Ammonia	19.22321	4470 036	***	0.131440	2369.119	***	6.151446 2369.119	3103.546	7367 961	28,47193	0.175508 67.59367	no
Ammonia Chlorides		4470 0.30			2.109.119		2309,119	3103.346	1301 901	28,47193	07.39367	กง กง
Sulfates					•••							no
TDS			•••									no
: :==*/	•											
	•••				***		•-•		•••			80
		•••				***					***	no

wqsmodn wk-l Developer Bruce Fielding	Date 03) Time: 10:45 A		Appendix B-	I			Page 1
Software 1,orus 4.0			LA0038709	, AF 19807			
Revision date: 02/14/05	Mar Arriba Ca		Charles O				
Innut coviublar	Water Quality Scree	en tot	City of DeOl	aincy WWTF			
Input variables		D1 .2 .			98 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
Receiving Water Characteristics:		Dilution:		0.1	Toxicity Dilution Series:		0.00.00.12
Barata Albara Maran	Day of Carel	ZID F ₅ =		0.1	Biomonitoring dilution:		0.894847
Receiving Water Name=	Buxton Creek 0,2	MZ Fs=		1	Dilution Series Factor:		0.75
Critical flow (Qr) cfs= Hann, mean avg tidal cfs=	0,2		Qr (MGD)=	0.12926			Percent Effluent
Drinking Water=1 HHNPCR=2			eun (MGD)=	0.12926	Dilution No. 1		89.485%
Marine, 1=y, 0=n		ZID Dilv		0.988386	Dilution No. 2		67,1135%
Rec Water Hardness=	119	MZ Dilu		0.894847	Dilution No. 3		50,3352%
Rec Water TSS=	4	HHne Di		0 894847	Dilution No. 4		37,7514%
Fisch/Specific=1,Stream=0		HHe Dil		0.894847	Dilution No. 5		28,3135%
Diffuser Ratio=		ZID Ups		0,011751			
		MZ Upsi		0.117509	Partition Coefficients; Dissolved	>'fotal	
Effluent Characteristics:			Upstream=	0.117509		*	
Permittee=	City of DeQuincy W	WTF			METALS	FW	
Permit Number=	LA0038709 ; Al 198	307			Total Arsenic	1.697907	
Facility flow (Ocf),MGD=	1.1	MZlihe U	Jpstream=	0,117509	Total Cadmium	4.340352	
		ZID Hai	dness=	•••	Chromium III	4,702401	•
Outfall Number =	001	MZ Hare	iness=		Chromium VI	1	
Eff. data, 2=lbs/day	2	ZID TSS	=		Total Copper .	2,491313	
MQL, 2≈lbs/day	2	MZ TSS	=	•••	Total Lead	4,694622	
Etiluem Hardness=	N/A	Multipli	ers:		Total Mercury	3,388414	
Effluent TSS=	N/A	WLAa -	> LTAa	0.32	Total Nickel	1.889369	
WQBL ind, 0=y, 1=n		WLAc -	> LTAc	0.53	Total Zinc	2,894646	
Acme:Chr. ratio 0=n, 1=y		LTA ac	>WOBL avg	1.31			
Aquatic, acute only 1=y,0=n		LTA a.c	>WQBI. max	3.11	Aquatic Life, Dissolved		
-		LTA h -	> WQBL max	2.38	Metal Criteria, ug/l.		
Page Numbering/Labeling		WOBL.	limit/report	2.13	METALS	ACUTE	CHRONIC
Appendix	Appendix B-1	WLA Fr	action	1	Arsenic	339,8	150
Page Numbers 1=y, 0=n	1	WQBL	Fraction	1	Cadmium	38,40101	1,172479
Input Page # 1*y, 0=n	ı				Chromium III	632.7587	
		Convers		. .	Chromium VI	15,712	10.582
Fischer/Site Specific inputs:		-	bs/day Qef	0.009174	Copper	21,70772	14,2526
Pipe=1 Canal=2 Specific=3			bs/day Oco	0.001668	Lead	78.00709 1.734	3.039824 0.012
Pipe width, feet ZID plume dist., feet		_	bs/day Qr >ug/L Qeo	109.0037	Mercury Nickel	1639,811	182,1142
MZ plume dist., feet		•	>սթե Qeն ->սթե Qeն	109,0037	Zinc	132.6224	121.1043
HHnc plume dist., feet		-	otl=y0=n	107,0057	2.1110	1,72,0224	121.1045
HHe plume dist., feet			>totl=y0*n	1	Site Specific Multiplier	Values:	•
		cfs>M	•	0,6463	C./. =		***
Fischer/site specific dilutions:					N =		
Dilution =	•••	Receivir	y Stream:		WLAa> LTAa		***
F/specific MZ Dilution =			Hardness=	25	WLAc> LTAc		
F/specific HHnc Dilution=	***	Default	TSS=	10	LTA a_c>WQBL avg		
F/specific HHe Dilution=		99 Crit.,	t=y, 0=n	ŧ	LTA a,c>WQBL max		***
					LTA h> WQBL max		

Appendix B-1 City of DeQuincy WWTF LA0038709 , At 19807 Page

(*1) (*2) (*3) (*4) (*5) (*fr) (*7) (8*) (*9) (*10) (*11) Toxic Cu Effluent Effluent MQL Effluent 95th % Numerical Criteria ш /Tech Parameters Instream Tech 1=No 95% estimate Acute Chronic HHNDW Careinogen 0=95 % Non-Tech FW EW Conc. (Avg) (Max) Indicator ug1. "C" ug/L lbs/day lbs/day lbs/day lbs/day ug/L աք Լ NONCONVENTIONAL Total Phenols (4AAP) 0.04587 700 350 50 3-Chlorophenol 0.09174 0.09174 4-Chlorophenol 383 192 2,3-Dichlorophenot 0.09174 0.09174 2.5-Dichlorophenol 2.6-Dichlerophenol 0,09174 3,4-Dichlerophenol 0.09174 2.4-Dichlorophenocyacetic acid (2,4-D) 2-(2,4,5-Trichlorophenovy) propionic acid (2,4,5-TP, Silvex) METALS AND CYANIDE Total Arsenic 0.09174 576.9487 254.686 **Total Cadmium** 0.0032 0.009174 0 0.006816 166.6739 5.088969 Chromium III 0.09174 2975.485 965.2166 Chromium VI 0.09174 15.712 10.582 0.09174 Total Copper 0.08 0.1704 54.08075 35.50768 0.04587 Total Lead 0.013 0.01769 366.2138 14.27083 Total Mercury 0.001835 5.87551 0.040661 Total Nickel 0.36696 3098.208 344.0809 Total Zinc 0.18348 383,8948 350,5541 Total Cyanide 0.18348 45.9 12844 DIOXIN 2,3,7,8 TCDD; dioxin 9.2E-08 7.2E-07 c VOLATILE COMPOUNDS 0.09174 1125 12.5 C 22.19 Benzene 0.09174 Bromoform 2930 1465 34.7 C Bromodichloromethane 0.09174 3,3 C Carbon Tetrachloride 0.09174 2730 1365 1.2 C 0.09174 2890 70 C Chloroform 1445 Dibromochloromethane 0.09174 5,08 Ç 1.2-Dichloroethane 0.09174 11800 5900 6.8 C 0.09174 0.58 \mathbf{c} 1,1-Dichloroethylene 1160 580 0.09174 303 1,3-Dichloropropylene 606 162.79 Ethylbenzene 0 09174 3200 1600 8100 Methyl Chloride 0.4587 55000 27500 Methylene Chloride 0.18348 19300 87 C 9650 1.1.2.2-Tetrachloro-0.09174 932 cthanc 466

Ethylbenzene

ethane

Methyl Chloride

Methylene Chloride

1.1.2.2-Tetrachloro-

3237.603 1788.015

30731,5

55646.3

19526.79

9051.824

10783.96 97.22329 6248.574

1036 033

17806.82

947.6477

16287,7

9051.824

942 9518 | \$20 7592 | 2 011516 | 301.7446 | 276 0024 | 2.011516 | 2.011516 | 2 011516 | 4 787409 | 0 018454 | 0 04392 | no

947.6477

16287,7 21336,88 50654,73

5715.5 97.22329 97.22329 97.22329 231,3914 0,891926 2.122785

1241,418 2947,184 11,38877 27,03747 no

195,7445 464,7065

Appendix B-1 City of DeQuincy WWTF LA0038709; AI 19807 Page

(* I) (*12) (*13) (*14) (*15) (*19) (*16) (*17) (*18) (*20) (*21) (*22) (*23) Toxic WLAa WLAc WLAB LTAa LTAc LTAh WQBL WQBL WQBL Limiting WOBL Need Parameters HHNDW Chronic Chronic HHNDW А,С,НН Max WQBI Acute Acute Avg Max Asg 001 100 001 001 ug / Lugʻl. ug/L սը4. ug/L սց/Լ. ug/Llbs/day 1bs'day ug l. սբ4. NONCONVENTIONAL Total Phenols (4AAP) 708.2256 391.1282 55.87545 226.6322 207.2979 55.87545 55.87545 55.87545 132.9836 0.512601 1.219991 3-Chlorophenol ---... ------4-Chlorophenol 387.5006 214.5617 ---124,0002 113 7177 ••• 113,7177 148 9702 353.6621 1.366653 3,244496 nο 2.3-Dichlorophenol ---------••• ... no 2.5-Dichlorophenol ---••• -----------------no 2,6-Dichlorophenol ••• ---------... ------11() 3,4-Dichlorophenol nο 2,4-Dichlorophenocyacetic acid (2,4-D) no 242.4.5-Trichlorophenoxy) propionic acid (2,4,5-TP, Silvey) nο METALS AND CYANIDE 583,7284 284,6139 Total Assenic 186.7931 150.8454 150 8454 197,6075 469,1292 1 812851 4,303791 Total Cadmium 168.6324 5.686969 53.96238 3.014094 3.014094 3.948463 9.373831 0.036223 0.085996 Chromium III 3010.45 1078.638 963.3439 571.6783 571.6783 748 8986 1777.92 6 870396 16,31063 ... Chromium VI 15,89663 11 82548 5,086922 6.267505 5.086927 6.663867 15.82033 0.061134 0.145136 ••• Total Copper 54.71624 39.68016 17.5092 21.03048 17.5092 22.93705 54.45361 ---0.210424 0.499557 Total Lead 370.5172 15.94778 118.5655 8.452323 ---8.452323 11.07254 26.28672 0.10158 0.241154 no Total Mercury 5.944552 0.045439 1.902257 0.024083 0.024083 0.031548 0.074897 0.000289 Total Nickel 3134.615 384.5135 1003,077 203,7922 ---203.7922 266,9677 633 7936 2,449162 5,814423 Total Zinc 388 4059 391 7474 124.2899 207.6261 ---124.2899 162.8197 386,5415 1,493708 3,546132 no 46.43937 6.034549 14353.29 14.8606 3.198311 14353.29 3.198311 4.189787 9.946747 0.038437 0.091251 Total Cyanide DIOXIN 8.05E-07 8.05E-07 8.05E-07 1.91E-06 7.38E-09 1.76E-08 no 2.3.7,8 TCDD; dioxin 8.05E-07 VOLATILE COMPOUNDS Benzene 2275.428 1257.198 13.96886 728,1369 666,3148 13,96886 13,96886 13,96886 33.2459 0.12815 0.304998 no Bromoform 2964,43 1637,151 38.77757 948.6177 867.6899 38.77757 38.77757 38,77757 92.29061 0.355745 0.846674 Bromodichloromethane 3.68778 3.68778 3.68778 3.68778 8 776916 0.033832 0.080519 1.341011 808.462 1.341011 1.341011 1.341011 3 191606 0.012302 0.02928 Carbon Tetrachloride 2762 08 1525.4 883.8656 Chloroform 2923.96 1614.801 78.22564 935,6672 855.8443 78.22564 78.22564 78.22564 186,177 0.717642 1.707988 5.676946 5.676946 5.676946 Dibromochloromethane 5.676946 13.51113 1,2-Dichloroethane 11938 66 6593.304 7.599062 3820,371 3494.451 7.599062 7.599062 7.599062 18 08577 0.069714 375.5619 343.5223 0.648155 1.1-Dichloroethylene 1173,631 648,1553 0.648155 0.648155 0.648155 1.54261 0.005946 0.014152 179,4608 196,1987 181.9193 179,4608 235.0936 1.3-Dichloropropylene 613.1211 338.6053 181.9193 558.123 2.156749 5.120221 no

TDS

Appendix B-1 City of DeQuincy WWFF LA0038709, AI 19807

(*1)	(*2)	•		. ,		-	(*8)	(*9)	(*10)	(*11)
Toxic		Effluent	Effluent	MQL	Effluent	95th %	Numerica			1111
Parameters	Instream	/Tech	/Tech		1=No 95%	•	Acute	Chronic	HHNDW	
	Conc.	, <u></u>			0=95 %	Non-Tech	FW	FW.		Indicator
	սե Ի	lbs/day	lbs'day	lbs/day		lbs/day	ng/L	ug/L	սլչժ.	"C"
VOLATILE COMPOUNDS (con	a'd)									
Tenachloroethylene				0.09174			1290	645	2.5	c
Toluene				0 09174			1270	635	46200	
1,1,1-Trichloroethane				0.09174			5280	2640		
1,1,2-Trichloroethane				0.09174			1800	900	69	C
Frichloroethylene				0.09174			3900	1950	21	C
Vinyl Chloride				0 09174					35.8	C
ACID COMPOUNDS										
2-Chlorophenol				0.09174			258	129	126,4	
2,4-Dichlorophenol				0.09174			202	101	232,6	
BASE NEUTRAL COMPOUND	s									
Benzidine				0,4587			250	125	0.00017	С
Hexachlorobenzene				0.09174					0.00025	c
Hexachlorabutadiene				0.09174			5.1	1,02	0.11	C
N. S.										
PESTICIDES										
Aldrin				0.000459			3		0 0004	C
Hexachlorocyclohexane										
(gamma BHC, Lindane)				0.000459			5.3	0.21	0.2	C
Chlordane				0.001835			2.4	0.0043	0 00019	C
4,4'-DD1				0,000917			1,1	0 001	0.00019	C
4,4'-DDE				0.000917			52.5	10.5	0.00019	C
1,1'-DDD				0.000917			0.03	0,006	0.00027	C
Dieldrin				0.000917			0.2374	0,0557	0.00005	C
Endosulfan				0.000917			0.22	0.056	0.64	
Endrin				0.000917			0.0864	0.0375	0.26	
Heptachlor				0.000459			0.52	0 0038	0.00007	С
Toxaphene		•		0.04587			0.73	0 0002	0 00024	c
Other Parameters:										
Fecal Col (col/100ml)									•	
Chlorine							19	H		
Аттопіа								4000		
Chlorides										
Sulfates										

Appendix B-1 City of DeQuincy WWTF LA0038709; Al 19807

y of DeQuincy WWTF

(*1) Toxic	(*12) WLAa	(*13) WLAc	(*14) WLAb	(*15) LTAa	(*16) LTAc	(*17) LTAh	(*18) Limiting	(* 19) WQBI.	(*20) WQBL	(*21) WQBL	(*22) (WQBL	Need
Parameters	Acute	Chronic	HHZDW	Acute	Chronic	HHVD#.	А.С.ИИ	Avg 001	Max 001	97A 100	Atax 1 001	wQBI
	ug t.	րեն.	upil.	սբւԼ	Aya.	ոեւ/Ր	սբԴ.	սբ Ն	ug/L	lbs'day	ibs day	
Tetrachloroethylene	1305,159	720.7934	2,793773	417.6508	382.0205	2.793773	2.793773	2 793773	6 649179	0 02563	0.061	no
Foluene	1284,924	709.6183	51628.92	411,1756	376 0977	51628.92	376.0977	492,688	1169.664	4.519919	10 7305	no)
1,1,1/Trichloroethane	53 12,045	2950.224	• • •	1709,454	1563.619		1563 619	2048,341	1862,851	18,79148	44.61182	no
1.1,2-Trichtoroethane	1821,152	1005.758	7 7 10813	582 7685	533.0518	7.710813	7,710813	7,710813	18,35173	0,070739	0.168359	no
Trichloroethylene	3945,829	2179,143	23 46769	1262,665	1154 946	23.46769	23.46769	23.46769	55,8531	0.215293	0.512396	no
Vinyl Chloride	***		40 00683			40,00683	40,00683	40,00683	95.21624	0.367023	0.873514	no
ACID COMPOUNDS												
2-Chlorophenol	261.0317	144,1587	141,2531	83,53016	76,4041	141.2531	76 4041	100.0894	237.0107	0.91822	2.179896	по
2,4-Dichlorophenol	204 3737	112,8684	259,9326	65,39958	59.82026	259 9326	59 82026	78.36454	186,041	0.718916	1.70674	no
BASE NEUTRAL COMPOUNT)S											
Benzidine	252,9377	139,6886	0.00019	80,94007	74 03498	0.00019	0.00019	91000.0	0.000452	1 74E-06	4.15E-06	no
Hexachlorobenzene			0,000279			0.000279	0.000279	0.00079	0.000665	2.5615-06	6 1E-06	no
Hexachlorabutadiene	5.15993	1,139859	0.122926	1.651177	0 604125	0.122926	0.122926	0.122926	0.292564	0 001128	0.002684	110
PESTICIDES							·					
Aldrin	3.035253	•••	0.000447	0.971281		0.000117	0.000447	0.000447	0.001064	4.1E-06	9.76E-06	no
Hexachlorocyclohexane												
(gamma BHC, Lindane)	5.36228	0 234677	0.223502	1.71593	0.124379	0.223502	0.124379	0.162936	0.386818	0.001495	0.003549	no
Chlordane :	2.428202	0.004805	0 000212	0.777025	0.002547	0.000212	0.000212	0.000212	0.000505	1,95E-06	4.64E-06	ng
4,4'-DDT	1112926	0.001118	0.000212	0.356136	0.000592	0.000212	0.000212	0.000212	0 000505	1.95E-06	4 64E-06	no
4.4'-DDE	53.11692	11.73385	0.000212	16.99742	6,218938	0.000212	0.000212	0.000212	0 000505	1,95E-06	4.64E-06	no
4,4'-DDD	0.030353	0.006705	0.000302	0.009713	0.003554	0.000302	0.000302	0.000302	0 000718	2.77E-06	6.59E-06	U ()
Dieldrin	0.24019	0.062245	5.59E-05	0.076861	0.03299	5.59E-05	5.59E-05	5.59E-05	0.000133	5,13E-07	1.22E-06	no
Endosutfan	0 222585	0.062581	0.715206	0.071227	0.033168	0.715206	0.033168	0.04345	0.103151	0 000399	0.000946	no
Endrin	0.087415			0.027973	0,02221					0.000267		no
Heptachlor	0.52611	0.004247	7.82E+05	0.100.00	0.002231	7.82E-05	7.82E-05	7.82E-05	0.000186	7.181:-07	1 71E-06	no
Toxaphene	0.738578	0.000224	0.000268	0.236345	0.000118	0.000268	0.000118	0,000155	0.000368	- 1,42E-06	3.38E-06	nο
Other Parameters:												
Fecal Col.(col/100ml)												no
Chlorine	19.22327	12.2926		6.151446	6.515078	•••	6.151446	8.058394	19.131	0.073928	0.175508	no.
Ammonia		4470,036			2369.119	•••	2369,119	3103,546	7367.961	28 47 193	67.59367	по
Chlorides												no
Sulfates	•••					•	***	•••		***		no
TDS	***		***	•••		•••		***		•••		no.
•						•	•••	•••	***	•••		no
			**-	•								no

WQBL CALCULATIONS FOR CITY OF DEQUINCY DEQUINCY WASTEWATER TREATMENT FACILITY LA0038709, AI 19807, PER20070002

DESIGN CAPACITY (Q_e): **1.1 MGD**CRITICAL LOW FLOW (7Q10): **0.2 cfs**HARDNESS VALUE: **119.0 mg/L**FIFTEENTH PERCENTILE VALUE FOR TSS: **4.0 mg/L**

PRIORITY POLLUTANT: ZINC

• Zn (Acute)
$$= e^{(0.8473 [\ln(\text{hardness})] \div 0.8604)} \text{ X CF}$$

$$= e^{(0.8473 [\ln 119] + 0.8604)} \text{ X 0.978}$$

$$= e^{(0.8473) (4.78) \div 0.8604)} \text{ X 0.978}$$

$$= e^{4.91} \text{ X 0.978}$$

$$= 135.61 \text{ X 0.978}$$

$$= 132.62 \text{ µg/L}$$

• Zn (Chronic) =
$$e^{(0.8473 [ln(hardness)] + 0.7614)} X CF$$

= $e^{(0.8473 [ln 119] + 0.7614)} X 0.986$
= $e^{(0.8473) (4.78) + 0.7614} X 0.986$
= $e^{4.811} X 0.986$
= $122.82 X 0.986$
= $121.10 \mu g/L$

DISSOLVED TO TOTAL METAL CONVERSION

$$\frac{C_D}{C_T} = \frac{1}{1 + (K_p) (TSS) (10^{-6})}$$

$$K_p = K_{po} X TSS^a$$

$$= 473,661.43$$

$$\frac{C_D}{C_T} = \frac{1}{1 + (473,661.43) (4) (10^{-6})}$$

$$= \frac{1}{2.89}$$

$$= 0.35$$

TOTAL =	$\underline{C_1} = 2.89$				
DISSOLVED	C_{D}				•
	DISSOLVED	X	$C_{\rm T}/C_{\rm D}$	=	TOTAL
Acute Criteria	132.62 μg/L	X	2.89	=	383.27 μg/L
Chronic Criteria	121.10 µg/L	X	2.89	=	349.98 μg/L
Human Health	5000 ng/I	X	2.89	· =	14 450 00 ng/L

DILUTION

	DISSOLVED	TOTAL
ACUTE	132.62 μg/L	383.27 μg/L
CHRONIC	121.10 μg/L	349.98 μg/L
HUMAN HEALTH	5000 μg/L	14,450.00 μg/L

DILUTION CALCULATIONS

DILUTION FACTOR =
$$Q_c$$

 $Q_r X F_s + Q_c$

• ZID (ACUTE) =
$$\frac{1.1 \text{ MGD}}{(0.2 \text{ cfs})(0.6463 \text{ MGD/cfs})(0.1 \text{ cfs}) + 1.1 \text{ MGD}} = 0.988$$

• MZ (CHRONIC) =
$$\frac{1.1 \text{ MGD}}{(0.2 \text{ cfs})(0.6463 \text{ MGD/cfs})(1 \text{ cfs}) + 1.1 \text{ MGD}} = 0.895$$

• HH (HUMAN HEALTH) =
$$\frac{1.1 \text{ MGD}}{(0.2 \text{ cfs})(0.6463 \text{ MGD/cfs}) + 1.1 \text{ MGD}} = 0.895$$

CONCLUDE THAT:

98.8% of effluent at edge of ZID 89.5% of effluent at edge of MZ 89.5% of effluent at edge of HH_{nc}

WASTELOAD ALLOCATION CALCULATIONS

WLA =
$$C_r = F_s X C_r X C_u$$
 $C_u = 0$

• WLA_{ZID} (ACUTE) =
$$\frac{383.27 \text{ µg/L}}{0.988}$$
 = 387.93 µg/L

• WLA_{MZ} (CHRONIC) =
$$349.98 \mu g/L$$
 = 391.04 $\mu g/L$ 0.895

• WLA_{HII} (HUMAN HEALTH) =
$$14.450 \mu g/L$$
 = 16,145.25 $\mu g/L$ 0.895

LTA CALCULATIONS

- $LTA_{ZID}(ACUTE)$ = $WLA_{ZID} \times 0.32$
 - = $387.93 \mu g/L \times 0.32 = 124.14 \mu g/L$
- LTA_{MZ} (CHRONIC) = WLA_{MZ} X 0.53
 - = $391.04 \mu g/L \times 0.53 = 207.25 \mu g/L$
- LTA_{HH} (HUMAN HEALTH) = $WLA_{HH} X I$
 - = $16,145.25 \mu g/L X 1 = 16,145.25 \mu g/L$

WQBL CALCULATIONS

LIMITING LTA = $124.14 \mu g/l$

- MONTHLY AVERAGE = LIMITING LTA X 1.31
 - = $124.14 \mu g/L \times 1.31$
 - $= 162.62 \,\mu g/L$
 - = 0.16262 mg/L X 1.1 MGD X 8.34 lbs/day = 1.49 lbs/day
- DAILY MAXIMUM = LIMITING LTA X 3.11
 - $= 124.14 \,\mu g/L \, X \, 3.11$
 - $= 386.08 \,\mu g/L$
 - = 0.038608 mg/L X 1.1 MGD X 8.34 lbs/day = 3.54 lbs/day

PRETREATMENT EVALUATION AND RECOMMENDATION

FACILITY NAME: City of DeQuincy WWTP

CITY:

DeQuincy

PARISH:

Calcasieu

PERMIT #:

LA0038709

DESIGN FLOW:

1.1 MGD

ACTUAL FLOW:

0.40 MGD

OTHER POTWS IN SYSTEM: N/A

SIGNIFICANT INDUSTRIES LISTED IN MANUFACTURERS GUIDE:

Industry Name	Type of Industry	Direct or Indirect Discharger
Caraustar Industrial	Manufactures tubes	N/A
Paragon Plastic Sheet Inc.	Manufactures unsupported plastics film and sheet	Indirect ²
S & I Wood Inc.	Sawing and planning mill	N/A 3
Southwestern Graphite/Asbury of Louisiana	Manufactures carbon and graphite products	Direct ⁴
United Oilfield Service Corp.	Oil and gas well construction, repair, and dismantling service	Indirect ²

STANDARD LANGUAGE RECOMMENDATION AND JUSTIFICATION:

Due to the absence of pretreatment categorical standards for the indirect discharges listed above or the discharge is of sanitary wastewater only, it is recommended that LDEQ Option 1 Pretreatment Language be included in LPDES Permit LA0038709. This language is established for municipalities that do not have either an approved or required Pretreatment program. This recommendation is in accordance with 40 CFR Part 403 regulations, the General Pretreatment Regulations for Existing and New Sources of Pollution contained in LAC Title 33, Part IX, Chapter 61 and the Best Professional Judgement (BPJ) of the reviewer.

¹ This facility is closed.

² The discharge is sanitary wastewater only.

³ This facility is located outside the City of DeQuincy limits and is therefore not connected to the POTW.

⁴ This facility is located outside the City of DeQuincy limits and is therefore not connected to the POTW. Sanitary wastewater from this facility is regulated via LDEQ General Permit LAG530041.

BIOMONITORING FREQUENCY RECOMMENDATION AND RATIONALE FOR ADDITIONAL REQUIREMENTS

Permit Number: LA0038709

Facility Name: City of DeQuincy

Previous Critical Biomonitoring Dilution: 89%
Proposed Critical Biomonitoring Dilution: 89%

Date of Review: 08/08/07 Name of Reviewer: Laura Keen

Recommended Frequency by Species:

Pimephales promelas (Fathead minnow): Once / Quarter¹ Ceriodaphnia dubia (water flea): Once / Quarter¹

Recommended Dilution Series: 28%, 38%, 50%, 67%, and 89%

Number of Tests Performed during previous 5 years by Species:

Pimephales promelas (Fathead minnow): 20

Daphnia pulex (water flea): N/A – Testing of species was not required Daphnia magna (water flea): N/A – Testing of species was not required

Ceriodaphnia dubia (water flea): 20

Number of Failed Tests during previous 5 years by Species:

Pimephales promelas (Fathead minnow): 4 lethal, 5 sub-lethal²

Daphnia pulex (water flea): N/A – Testing of species was not required N/A – Testing of species was not required

Ceriodaphnia dubia (water flea): 1 lethal, 3 sub-lethal²

Failed Test Dates during previous 5 years by Species:

Pimephales promelas (Fathcad minnow): 12/1/02-2/28/03 (lethal & sub-lethal); 1/1/03-

3/31/03 (lethal & sub-lethal); 12/1/03-2/29/04 (lethal & sub-lethal); 3/1/04-5/31/04 (lethal &

sub-lethal); 6/1/04-8/31/04 (sub-lethal)

Daphnia pulex (water flea):N/A – Testing of species was not requiredDaphnia magna (water flea):N/A – Testing of species was not requiredCeriodaphnia dubia (water flea):9/1/05-11/30/05 (sub-lethal); 11/1/05-1/31/06

(sub-lethal); 3/1/07-5/31/07 (lethal & sub-lethal)

Previous TRE Activities: N/A – No previous TRE Activities

¹ Due to significant lethal and sub-lethal failures to the *Ceriodaphnia dubia* and *Pimephales promelas*, this facility shall have an established biomonitoring testing frequency of once per quarter for *Ceriodaphnia dubia* and *Pimephales promelas* for the tife of the permit.

Due to discrepancies noted in the biomonitoring DMRs, LDEQ requested the biomonitoring lab reports on July 20th, 2007, from this facility. As of the date of this recommendation, these lab reports have not been received.

Additional Requirements (including WET Limits) Rationale / Comments Concerning Permitting:

The City of DeQuincy Wastewater Treatment Facility owns and operates an existing publicly owned treatment works serving the city of DeQuincy in DeQuincy, Calcasicu Parish, Louisiana. LPDES Permit LA0038709, effective March 1, 2001, contained chronic freshwater biomonitoring as an effluent characteristic of Outfall 001 for *Pimephales promelas* and *Ceriodaphnia dubia*. The effluent series consisted of 28%, 38%, 50%, 67%, and 89% concentrations, with 89% being defined as the critical dilution. Testing was to be performed once every quarter. Data on file indicate that the permittee has complied with the biomonitoring requirements contained in LA0038709 with DMR results showing 1 lethal and 3 sub-lethal failures to the *Ceriodaphnia dubia* and 4 lethal and 5 sub-lethal failures to the *Pimephales promelas* from toxicity testing during the last five years.

It is recommended that freshwater chronic biomonitoring continue to be an effluent characteristic of Outfall 001 (discharge of 1.1 mgd of treated sanitary wastewater) in LA0038709. The effluent dilution series shall be 28%, 38%, 50%, 67%, and 89% concentrations, with 89% being defined as the critical biomonitoring dilution. In accordance with the Environmental Protection Agency (Region 6) WET testing frequency acceleration(s), the biomonitoring frequency shall be once per quarter for *Pimephales promelas* and *Ceriodaphnia dubia*.

This recommendation is in accordance with the LDEQ/OES Permitting Guidance Document for Implementing Louisiana Surface Water Quality Standards, EPA Region 6 Post-Third Round Whole Effluent Toxicity Testing Frequencies (Revised June 30, 2000), and the Best Professional Judgement (BPJ) of the reviewer.